


Oil Pattern Distance	38	Reverse Brush Drop	38	Oil Per Board	50 ul
Forward Oil Total	11.7 mL	Reverse Oil Total	16.5 mL	Volume Oil Total	28.2 mL
Tank Configuration	Multi Tank	Tank A Conditioner	Fire	Tank B Conditioner	Fire

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	3	18	3	A	111	0.0	5.1	5.1	5550
2	6L	6R	2	18	3	A	58	5.1	10.2	5.1	2900
3	11L	11R	2	18	3	A	38	10.2	15.3	5.1	1900
4	16L	16R	3	18	3	A	27	15.3	22.9	7.6	1350
5	2L	2R	0	18	3	A	0	22.9	38.0	15.1	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	B	0	38.0	28.0	-10.0	0
2	11L	11R	1	18	3	B	19	28.0	25.5	-2.5	950
3	10L	10R	2	14	3	B	42	25.5	21.6	-3.9	2100
4	9L	9R	2	14	3	B	46	21.6	17.7	-3.9	2300
5	7L	7R	2	14	3	B	54	17.7	13.8	-3.9	2700
6	5L	5R	2	10	3	B	62	13.8	11.0	-2.8	3100
7	3L	3R	2	10	3	B	70	11.0	8.2	-2.8	3500
8	2L	2R	1	10	3	B	37	8.2	6.8	-1.4	1850
9	2L	2R	0	10	3	B	0	6.8	0.0	-6.8	0



Cleaner Ratio Main Mix NA Forward
 Cleaner Ratio Back End Mix NA Reverse
 Cleaner Ratio Back End Distance NA Combined
 Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	2.62	1.38	1.09	1.09	1.38	2.62

